

LIMELIGHT® COLLECTION

PULSE®



7 49 Open 230

People Jets Seating Voltage

7′5″ x 7′5″ x 38″

FreshWater® Salt System Ready

Dimensions Water Care

LIMELIGHT® COLLECTION







Shell Colors







7 people







Cabinet Colors







Cover Colors





Alpine White

Ice Gray

Platinum

Desert

Tuscan Sun

Coastal Gray

Espresso

Slate Caramel

Chestnut

Seating Capacity

Dimensions

7'5" x 7'5" x 38" / 2.26 m x 2.26 m x 0.97 m

Water Capacity

445 gallons / 1,685 liters

Weight

1,015 lbs. / 460 kg dry; 5,950 lbs. / 2,700 kg filled*

Jets

• 1 XL Dual Rotary jet

• 1 XL Single Rotary jet

• 2 XL Directional jets

• 4 Standard Single Rotary jets

• 2 Standard Directional jets

• 4 Rotary Precision jets

• 35 Directional Precision® jets

Water Feature

Vidro® backlit ribbon waterfall

Jet Pump 1

Wavemaster® 9200; Two-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque

Jet Pump 2

Wavemaster® 9000; One-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque

SilentFlo 5000® for quiet, continuous filtration

Circulation Pump

Water Care System FreshWater® Salt System Ready **Control System**

IQ 2020® with LCD control panel

230 V / 50 amp, 60 Hz

(Includes G.F.C.I. protected sub-panel)

Lighting System

Raio® multi-color interior points of light Exterior multi-color lighting with timer

Heater

Titanium No-Fault® 4,000 W / 230 V

Energy Efficiency

FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14

Filtration System

energy efficiency standards for portable spas

Dual action, 100 sq. ft., top loading 3.5" to 2.5" tapered, 2 lb. density foam core

Vinyl Cover

Available Options

Cover Lifter

CoverCradle®, CoverCradle II, Lift 'n Glide®,

or UpRite®

CoolZone™

Steps

Limelight Collection Step (Coastal Gray, Espresso, and Sable), Polymer Step (Ash)

Entertainment

Hot Tub Cooling System

Bluetooth® Wireless Sound System

Actual colors and products may vary from print representation. See dealer to verify.

 * Includes water and 7 adults weighing 175 lbs. each. Export models available in 240 V, 50 Hz, 1,500 W heater.